



10 x 28 EXTRA-FLOW PRODUCT DATA SHEET






Sanitary connections are only available on 316 SS. A complete drawing is available on the web site.
Note: Overall length does change.



All dimensions are nominal values

Membrane Characteristics			
Cartridge Configuration		Extra-Flow with Center Baffle	
Liquid Flow Guidelines		X50: 10 – 48 m ³ /hr (44 – 210 gpm) X40: 10 – 57 m ³ /hr (44 – 250 gpm)	
Membrane Type		X50 Fiber	X40 Fiber
		Recommended for CO ₂ removal from liquid and other gas transfer applications	Recommended for O ₂ removal from liquid and other gas transfer applications
Membrane/Potting Material		Polypropylene / Epoxy	
Typical Membrane Surface Area		130m ² (1400 ft ²)	
Priming Volume (approximate)		X50 Fiber FRP Housing	X40 Fiber FRP Housing
		X40 Fiber 316 SS Sanitary/316 SS ANSI	
	Shellside	26.1 L (6.9 gal)	26.3 L (7.0 gal)
	Lumenside	10.6 L (2.8 gal)	9.5 L (2.5 gal)
Pressure Guidelines*		X50 Fiber	X40 Fiber
Maximum Shellside LIQUID Working Temperature/ Pressure		5-50° C, 7.2 bar (41-122° F, 105 psig) 70° C, 2.1 bar (158° F, 30 psig)	5-25° C, 9.3 bar (41-77° F, 135 psig) 50° C, 7.2 bar (77-122° F, 105 psig) 70° C, 2.1 bar (158° F, 30 psig)
If no vacuum is used, 1.05 bar (15 psig) can be added to pressures above.			
Maximum Applied Gas Pressure		FRP	316 SS
		6.2 bar (90 psig)	9.0 bar (130 psig)
Max applied gas pressure is for integrity testing at ambient temperatures. Normal operating pressures are typically lower.			
*Pressures are based on non-dangerous liquids and gasses per the European Union Pressure Equipment Directive /97/23/EC. See Operating Guide for pressure limits in the European Union with dangerous liquids and gasses. Also, see Operating Guide for complete temp/pressure limits for housings and membrane. Note: Liquid pressure should always exceed gas pressure.			
Housing Options and Characteristics			
Material	Fiber Reinforced Plastic (FRP) with PVDF for all wetted surfaces and FRP flanges	316L SS Vessel/CF3M SS End Caps. ≤ 32RA on schedule 10S pipe per ASTM A312. 0.8µm SI.	
Flange Connections			
Shellside (Liquid Inlet/Outlet)	<ul style="list-style-type: none"> • 3 inch class 150 raised face flange per ANSI B16.5 • 80A at 10K flat face flange per JIS B2238 • 3 inch sanitary flange available on 316L SS fine finish 		
Lumenside	<ul style="list-style-type: none"> • 1 inch class 150 raised face flange per ANSI B16.5 • 50A at 10K flat face flange per JIS B2238 • 1.5 inch sanitary flange available on 316L SS fine finish 		
Mounting Kit			
A Mounting Kit with 2 cradles and 2 straps is available and sold separately. It will hold the contactor horizontally or vertically.			
Seal Options			
Material	Applications		
EPDM (ANSI / NSF 61, FDA CFR title 21 Compliant) [†]	All Purpose		
HP1 Viton	High Purity/Electronics		
Weight			
	FRP Housing	Stainless Steel Housing	
	ANSI/JIS	ANSI /JIS	Sanitary
Dry	33 kg. (73 lbs.)	93 kg. (204 lbs.)	81 kg. (177 lbs.)
Liquid Full (shellside)	57 kg. (126 lbs.)	115 kg. (253 lbs.)	107 kg. (235 lbs.)
Cartridge only – dry	10 kg. (23 lbs.)	10 kg. (23 lbs.)	10 kg. (23 lbs.)
Shipping weight (max)	44 kg. (98 lbs.)	150 kg. (330 lbs.)	138 kg. (303 lbs.)
Regulatory			
Meets RoHS threshold limits. Complies with the PED 97/23/EC. NSF certified to NSF/ANSI 61 with EPDM o-rings. CFR Title 21 compliant. For FDA compliance on the FRP PVDF lined vessel 20,000 gallons of liquid should be flushed through the contactor prior to use.			

10 x 28 EXTRA-FLOW PRODUCT DATA SHEET



Cartridge Specifications		
Characteristics	Test Conditions	Specifications
Performance O ₂ Removal	Shellside water flow: 36.3 m ³ /hr (160 gpm), 20°C (68°F) Lumenside N ₂ Flow: 10.3 Nm ³ /hr, 0°C, 1 atm (6.5 ft ³ /min, 20°C [68°F], 1.0 atm)	X40 : 83.2% minimum
		X50 : 81.3% minimum
Pressure Drop	Shellside water flow: 36.3 m ³ /hr (160 gpm), 20°C (68°F)	X40 : 0.41 bar (6.0 psi) maximum
		X50 : 0.48 bar (6.9 psi) maximum

Curves represent nominal values using water. Characteristics may change under different operating conditions.

Test condition O₂ Removal with X40 membrane 20°C (68°F): N₂-vacuum combo mode, vacuum: 50 mm Hg N₂ sweep flow 0.40 Nm³/hr (0.25 scfm).

Test condition CO₂ Removal with X50 membrane 25°C: Air-vacuum combo mode, vacuum 75 mm Hg, air sweep flow 1.6 Nm³/hr (1 scfm).

NOTE: All dimensions on the front of this data sheet are nominal values.

This product is to be used only by persons familiar with its use. It must be maintained within the stated limitations. All sales are subject to Seller's terms and conditions. Purchaser assumes all responsibility for the suitability and fitness for use as well as for the protection of the environment and for health and safety involving this product. Seller reserves the right to modify this document without prior notice. Check with your representative to verify the latest update. To the best of our knowledge, the information contained herein is accurate. However, neither Seller nor any of its affiliates assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Determination of the suitability of any material and infringement of any third party rights, including patent, trademark, or copyright rights, are the sole responsibility of the user. Users of any substance should satisfy themselves by independent investigation that the material can be used safely. We may have described certain hazards, but we cannot guarantee that these are the only hazards that exist. Nothing herein shall be construed as a recommendation or license to use any information that conflicts with any patent, trademark or copyright of Seller or others. Please read our Operating Manuals carefully before installing and using these modules.

THE INFORMATION CONTAINED HEREIN AND SELLER'S PRODUCTS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR USE, OR NON-INFRINGEMENT OF INTELLECTUAL PROPERTY. IN NO EVENT SHALL SELLER BE LIABLE FOR ANY SPECIAL, INCIDENTAL, INDIRECT, OR CONSEQUENTIAL DAMAGES OF ANY KIND, OR ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF INFORMATION CONTAINED HEREIN AND SELLER'S PRODUCTS.

Liqui-Cel®, SuperPhobic®, MiniModule®, and MicroModule® are registered trademarks of Membrana-Charlotte, A Division of Celgard, LLC.

Copyright © 2012 Membrana – Charlotte All rights reserved. (D61_10x28 Rev23)



ISO 9001
ISO 14001

Membrana - Charlotte
A Division of Celgard, LLC
13800 South Lakes Drive
Charlotte, North Carolina 28273
USA

Phone: (704) 587 8888
Fax: (704) 587 8610

Membrana GmbH
Oehder Strasse 28
42289 Wuppertal
Germany

Phone: +49 202 6099 - 658
Phone: +49 6126 2260 - 41
Fax: +49 202 6099 - 750

Membrana-Japan
Polypore K.K.
Shinjuku Mitsui Building, 27F
1-1, Nishishinjuku 2-chome
Shinjuku-ku, Tokyo 163-0427
Japan

Phone: 81 3 5324 3361
Fax: 81 3 5324 3369



www.liqui-cel.com